

SUPERIOR PERFORMANCE, EFFORTLESS OPERATION

KEY BENEFITS



ENGINEERED FOR UNMATCHED RELIABILITY

Unparalleled accuracy with proprietary DVX[®] pump technology, enhanced dispense consistency with shorter tubing, and improved stirring and colorant conditioning with innovative blade design



BUILT TO PERFORM AND LAST

33% faster throughput than AT1600, no recalibration required, and dispense speed of up to 28 oz per minute



EQUIPPED FOR MINIMAL AND EASY SERVICE

Easier access to pumps and canisters with an external power switch, eliminating the need to open the machine



DESIGNED WITH OPERATOR CONVENIENCE IN MIND

Improved 3-liter canisters, a new can shelf with can locator LEDs, and a center dispensing chassis



ONE-OF-A-KIND PUMP TECHNOLOGY

DVX® pump technology puts Accutinter dispensers head and shoulders above the rest:

- Robust construction eliminates component wear
- Valveless design eliminates need for annual calibration, and alleviates need for maintenance
- State-of-the-art electronics provide unmatched speed
- Builds on IDEX experience in designing durable and accurate pumps for health, fire, rescue applications

DRIVEN BY COLORPRO 5 SOFTWARE

ColorPro 5 software optimizes the performance of your Accutinter dispensers:

- Automates paint tinting and record-keeping
- Reduces mistints through operator prompts
- Prolongs equipment life with maintenance recommendations
- Features a friendly graphical interface


SERVICE & SUPPORT

Our customer commitment continues long after the sale with:

- Prompt installation and training
- Factory technicians in the US/Canada
- Unmatched, factory-certified Authorized Service Network
- Preventive Maintenance and Extended Warranty programs
- YouTube channel with how-to videos

Scan this QR code

to learn more about the product



TECHNICAL SPECIFICATIONS

Dispensing	Simultaneous dispense- 2 colorants at a time
Dispense Location	Center Dispense
Max Flow Rate	Up to 28 oz/minute with optimized mapping for throughput
Nozzle Closure	Manual
Accuracy	1/512th minimum (colorant dependent)
Shelving	Manual Adjustable with positioning for sample, quart, 1-gallon, and 5-gallon containers (lightweight shelf)
Colorant Compatibility	Universal, waterborne, and organic
Canister Quantity	16 Canisters
Canister Capacity	3 quarts/3 liters (large diameter)
Dimensions (WxDxH)	35" x 28" x 44"
Power	Dual Voltage- 110/220v 50/60Hz
Safety	UL, CSA, FCC
Canister Locating Light	16 Improved LEDs
Serviceability	No Re-Calibration Needed
Software	ColorPro software keeps the paint department running smoothly
	IDEX Dispenser Driver- accompanies the customer-designer in-house software programs to interact with the dispenser
Available Accessories	Computer and 19" Monitor
	Barcode Scanner
	Label Printer
	Scanner/Label Printer Tray
	Surge Protector
	Can/Lid Sealer

